

DEFENDER SUPREME



Features

- Strong and seamless body with fully welded multi-corner bend construction without a single rivet and one-piece wrap around door construction
- Two-step door and frame construction for higher resistance against fire and burglary
- Lift-off hinges door construction which facilitates removal of door for ease in transportation & in service
- Armoured with Double Duty Barrier (DDB) material in the door and the body
- Enhanced Torch and Drill Resistant (TDR) Matrix used in TRTL classes of safes
- Strong shooting bolts to secure the door behind the jamb box against dislodging
- Additional relocking device provided beyond the standard BIS for extra protection against attack through keyhole
- Dual control high precision 8-lever locks protected with unique drill-defeat shield in the door
- Class C safes have successfully withstood the one-hour fire resistance test carried out at C.B.R.I., Roorkee, India.
- Tested as per BIS standard IS 550:2014

Specifications

Model No.	Dimensions	External Dimensions (H x W x D)	Internal Dimensions (h x w x d)	Weight in Kgs	Volume in (Ltrs./Cu ft.)
26	mm	660 x 53 x 565	460 x 330 x 295	kgs 395	Ltrs 44.78
	Inches	26 x 20 ^{7/8} x 22 ^{1/4}	18 ^{1/8} x 13 x 11 ^{5/8}	lbs 871	Cuft 1.58
31	mm	790 x 630 x 665	585 x 430 x 395	kgs 600	Ltrs 99.36
	inches	31 ^{1/8} x 24 ^{13/16} x 26 ^{1/8}	23 x 16 ^{7/8} x 15 ^{9/16}	lbs 1323	Cuft 3.51
41	mm	1040 x 630 x 665	840 x 430 x 395	kgs 760	Ltrs 142.67
	inches	41 x 24 ^{13/16} x 26 ^{1/8}	33 ^{1/8} x 16 ^{7/8} x 15 ^{9/16}	lbs 1676	Cuft 5.04
49	mm	1245 x 785 x 715	1045 x 585 x 435	kgs 1065	Ltrs 265.93
	inches	49 x 24 ^{7/8} x 28 ^{1/8}	41 ^{1/8} x 23 x 17 ^{1/8}	lbs 2348	Cuft 9.39
61SD	mm	1550 x 785 x 715	1350 x 585 x 435	kgs 1300	Ltrs 343.54
	inches	61 x 30 ^{7/8} x 28 ^{1/8}	53 ^{1/8} x 23 x 17 ^{1/8}	lbs 2866	Cuft 12.13

All weights and sizes are approximate. Tolerances - Weight \pm 10%, Dimensions \pm 5%
 *61DD is not rated as per UL and is available in standard Defender Plus Safe model.